

METHANE PLASMALYSIS

Production of hydrogen and carbon black

Methane plasmalysis is the **key technology for producing large quantities of high-purity hydrogen from natural gas** with only a quarter of the energy required for electrolysis. With the methane plasmalysis process developed by Graforce, the methane (CH₄) is not broken down catalytically or at very high temperature, but rather **split into its molecular components hydrogen (H2) and carbon (C)** using a plasma. For example, four kilograms of methane and 10 kWh of electricity produce 1 kg of hydrogen and 3 kg of elemental carbon.

When biomethane is used for plasmalysis, **carbon dioxide** is removed from the atmosphere. Thus, Graforce offers a real alternative to the controversial CCS storage of CO₂.

ONTACT

Graforce GmbH Johann-Hittorf-Str. 8 12489 Berlin, GERMANY Phone.: +49 (0)30 63 2222 110 Fax: +49 (0)30 63 2222 129 info@graforce.de www.graforce.de



•

GRAFORCE



PLANT SOLUTION

Graforce uses methane plasmalysis to decarbonize the natural gas. The resulting hydrogen in combination with a hydrogen CHP or fuel cell enables CO₂-free heat and power generation.

The solid carbon can be used as an industrial raw material, for the production of steel, carbon fibers and other carbon-based structures and materials, for example.



PLASMALYSE-TECHNOLOGIE

In methane plasmalysis, a non-thermal plasma is used to convert natural gas or biomethane into hydrogen and solid carbon with very little energy input and without producing CO₂. The non-thermal plasma is generated by a high-frequency electric field, which leads to the ionization of the methane. The electrons inside reach temperatures of 10,000 to 100,000 K (1-10 eV) and determine the decomposition process of the methane, while the gas temperature remains as low as room temperature.

With electricity from renewable energies, methane plasmalysis is just as climate-friendly as electrolysis, but at a much lower cost.





APPLICATIONS APPLICATIONS

Methane plasmalysis plants with capacities from 115 to $6,500 \text{ Nm}^3 \text{H}_2/\text{h}$ have been designed for the following industries:

>> Heavy duty traffic

- >> Steel industry
- >> Fertilizer industry
- >> Energy and heat industry



SPECIFICATIONS

Feed:

Natural gas, biomethane

Measurements:

20 foot container (6058mm/2438mm/2591mm)

optional:

Container for compression (4000mm/2000mm/2591mm)

Power range:

115 – 6.500 Nm³/h (< 600 Nm³/h in container)

H₂ purity: Usually 98% vol.

(optionally 99.9999% vol.)

H₂ delivery pressure: Typically 2 – 10 bar

Resources:

For the production of 115 Nm³/h H₂ from natural gas, the following operating materials are required or produced:

- 60 Nm³/h of methane
- 138 kWh of electricity

By-product:

- 30 kW of heat
- 30kg of carbon black

Carbon Black:

Purity: 98% by weight (with natural gas as feed) Particle size: 10-150 µm (depending on the plasma parameters) Surface: 80 g/m² (BET nitrogen adsorption)

Product forms:

- Compressed powder
- Granules
- Pellets